

AS162R5SP6000

161.5 – 163.5 MHz / 6000 Watts



SUNGSAN

Electronics & Communications Co., Ltd.

ELECTRICAL SPECIFICATIONS @ 220VAC, 20°C, 50Ω System

Parameter	Note	Specifications
Operating Frequency	BW	161.5 ~ 163.5 MHz
Output Power CW	PSAT	Min. 6000 Watts
Input Impedance	Ω	50 ohm
Power Gain	Gp	Typ. 68 dB
Power Gain Flatness	Gripp	Typ. ± 0.5 dB
Gain Linearity	Li	Max. 0.5dB
Input Power for Rated PSAT	PIN	Typ. 0 dBm
Efficiency	Eff	Min. 60%
Input VSWR	S ₁₁	Max 2.0:1
Harmonics @ P _{OUT} = 5000W	2ND,3RD	Max -40dB
Spurious Signal	Spur	Max. -70dB
Power Stability	G _{stab}	Max. $\pm 0.5\%$ (Peak to Peak)
Phase Stability	P _{stab}	Max. ± 0.5 deg
Primary Power		200-260VAC, 50/60Hz, Single phase

MECHANICAL SPECIFICATIONS

Parameter	Value	Note
Dimensions, H x W x D	1900 X 600 X 1800mm	19" Rack
Weight	TBD	kg
RF Input	SMA, Female	
RF Output	EIA 3-1/8, Female	
Cooling	Water cooling system	-

ENVIRONMENTAL CHARACTERISTICS (Design to Meet)

Parameter	Symbol	Specifications	Unit
Operating Water Temperature	TA	+10 ~ +35	°C
Non-operating Temperature	TSTG	0 ~ +50	°C
Relative humidity	RH	95 Max.	%

AS162R5SP6000

161.5 – 163.5 MHz / 6000 Watts



SUNGSAN

Electronics & Communications Co., Ltd.

MONITORING & CONTROL

Description	Specifications	Note
RS-232	Serial management of device /local operator	D-sub 9pin
Status Monitor	FWD/REV Power indication & Alarm indication Standby mode, Fault indication & Temperature	LCD Controller
Gain Adjustment	Gain Adjustment	Front Panel

LIMITS

Parameter	Specifications	Unit
Input RF drive level without damage	+5 dBm	Max
Over Temperature Alarm	50°C	Max
VSWR Protection	∞ @ all load phase & amplitude for duration of 1 minute 3:1 @ all load phase & amplitude continuous	

SYSTEM OUTLINE

